

**ROTEX**

For wall mounting. External rotor motor

**Medium-sized, low sound level, regulation from 0 to 100%.****Applications:** Industrial cold storage machinery, large premises, warehouses.**CHARACTERISTICS**

- IP 54 motors, class F.
- Thermoplastic plus fiber glass frame.
- Plate epoxy-paint finished frame.
- Working temperature from -30°C to 70°C.
- Air direction: motor - impeller.

**OPTIONS:**

- Can be supplied without frame.
- Air direction: impeller - motor.

230V 50Hz (I~) 1.400 r.p.m. (n: min-1) Ø 315 - 450 mm

		Ø mm	m <sup>3</sup> /h	Amp.	W	dB (A)	ACCESSORIES			Price €	
								DS	PG		PS
<b>ROTEX 4-315M</b>	AR4031M	315	1.600	0,40	80	57	•	•	•	•	*
<b>ROTEX 4-355M</b>	AR4035M	355	3.000	0,60	120	59	•	•	•	•	*
<b>ROTEX 4-400M</b>	AR4040M	400	4.500	0,90	180	63	•	•	•	•	*
<b>ROTEX 4-450M</b>	AR4045M	450	6.600	1,20	230	66	•	•	•	•	*

400V 50Hz (III~) 1.400 r.p.m. (n: min-1) Ø 315 - 450 mm

		Ø mm	m <sup>3</sup> /h	Amp.	W	dB (A)	ACCESSORIES			Price €	
								DS	PG		PS
<b>ROTEX 4-315T</b>	AR4031T	315	1.600	0,25	80	57	•	•	•	•	*
<b>ROTEX 4-355T</b>	AR4035T	355	3.000	0,35	130	59	•	•	•	•	*
<b>ROTEX 4-400T</b>	AR4040T	400	4.500	0,40	180	63	•	•	•	•	*
<b>ROTEX 4-450T</b>	AR4045T	450	6.600	0,60	240	66	•	•	•	•	*

\* Consulting price


**ACCESSORIES**

## ■ Regulation



(pg. 180 to 183)

## ■ Accessories equipments

**DS** (pg. 186) **PG** (pg. 186) **PS** (pg. 187)